

## **Technical Specification**

RadioCam	Specifications
Dimension	85*58*29 (mm)
Weight	130g
IP Rating	IP66
Compatible Radio Model	Motorola
	M5: GP328plus, GP338plus, GP344, GP388, PTX760Plus, EX500, EX600, GL2000
	M7: DP4000, DP4400, DP4600, DP4401, DP4601; DP3400/3401/3600/3601 XPR6300, XPR6500, XPR6550, XiRP8268, XiRP8608, XiRP8668, XiRP8200, XiRP8208, MTP850S;
	M11: XPR3300, XPR3500, XiRP6600, XiRP6620, DP2000/2400/2600, DP3441 MTP3000/3500/3550
	M1: DP1400 Series
	TeloPTT Device: TE580, TE590
	Hytera
	H5: PD70X, PD78X, PT580H, PT580H Plus
	H8: PD60X/66X/68X, X1e/X1p/Z1p
	<b>Sepura SP2:</b> STP8000/9000 Series
	Airbus: THR9, TH9, TH1N
	Kenwood
	K2: TK-280,TK-290,TK-380,TK-385,TK-390, TK-480,TK-481,TK-2140, TK-2180, TK-314 TK-3148, TK-3180, TK-5210, TK-5400, TK-5310, NX-200/300
Camera	
Resolution	1920*1080P, 1280*720P
resolution	1828 18881, 1288 7281
	140 Degrees
Field of View	
Field of View Night Vision	140 Degrees
Field of View  Night Vision  Built-in Storage	140 Degrees Support
Field of View  Night Vision  Built-in Storage  Low Memory Alarm	140 Degrees  Support  32GB Standard, 64/128GB Option
Field of View  Night Vision  Built-in Storage  Low Memory Alarm  Operating Temperature	140 Degrees  Support  32GB Standard, 64/128GB Option  Support
Field of View Night Vision Built-in Storage Low Memory Alarm Operating Temperature Recording	140 Degrees  Support  32GB Standard, 64/128GB Option  Support
Field of View Night Vision Built-in Storage Low Memory Alarm Operating Temperature Recording	140 Degrees  Support  32GB Standard, 64/128GB Option  Support  -20° C ~ + 50 ° C
Field of View Night Vision Built-in Storage Low Memory Alarm Operating Temperature Recording Video Quality	140 Degrees  Support  32GB Standard, 64/128GB Option  Support  -20° C ~ + 50 ° C  Multiple Recording Resolutions
Field of View Night Vision Built-in Storage Low Memory Alarm Operating Temperature Recording Video Quality Recording Format	140 Degrees  Support  32GB Standard, 64/128GB Option  Support  -20° C ~ + 50 ° C  Multiple Recording Resolutions 1920x1080p (30 FPS); 1280x720p (30 FPS)
Field of View Night Vision Built-in Storage Low Memory Alarm Operating Temperature Recording Video Quality  Recording Format Date & Time Stamp Low Battery Alarm	140 Degrees  Support  32GB Standard, 64/128GB Option  Support  -20° C ~ + 50 ° C  Multiple Recording Resolutions 1920x1080p (30 FPS); 1280x720p (30 FPS)  H.264 .MP4
Field of View Night Vision Built-in Storage Low Memory Alarm Operating Temperature Recording Video Quality Recording Format Date & Time Stamp	140 Degrees  Support  32GB Standard, 64/128GB Option  Support  -20° C ~ + 50 ° C  Multiple Recording Resolutions 1920x1080p (30 FPS); 1280x720p (30 FPS)  H.264 .MP4  Yes

Photo	
Taking Photo	Support
Battery	
Туре	3000mAh Lithium Polymer Rechargeable Battery
Charging Time	4.5 Hours
Battery Life	9 Hrs Continuous@720p; 8 Hrs Continuous@1080p;
Low Battery Alarm	Support
Security	
Password Protect	6 Digit Security Code

## **Standard Accessories**







Belt Clip



**Power Plug** 

## **Option Accessories**



**Dock Epaulette** 



Camera Radio Cable



Single Unit Charger



**Centre Chest Harness** 



**Chest Harness** 



**Dock Clamp** 

## Reliable and Flexible

4/F, Chuangye Building, Seven-Star Park, Yu'an 2nd Road, Bao'an District, Shenzhen, China Tel: +86 755 86950766

Fax: +86 755 86950708

Email: sales@telosystems.com